

# HTG

## 680 RC ULTRA

TECHNICAL SHEET:

FLOOR GRINDER



|                               |                |
|-------------------------------|----------------|
| GRINDING WIDTH                | 680 mm         |
| GRINDING DISC DIAMETER        | 230 mm         |
| NUMBER OF GRINDING HEADS      | 3 or 4         |
| OUTPUT POWER                  | 11,0 kW        |
| VOLTAGE                       | 400 V          |
| RATED CURRENT                 | 20 A           |
| FREQUENCY                     | 50/60 Hz       |
| TYPE                          | Remote-control |
| DIRECTION OF ROTATION         | Right/Left     |
| GRINDING HEAD SPEED MIN (RPM) | 300            |
| GRINDING HEAD SPEED MAX (RPM) | 900            |

|                        |               |
|------------------------|---------------|
| MAX. GRINDING PRESSURE | 325 kg/335 kg |
| ELECTRICAL CONNECTION  | 32 A - 400 V  |
| VACUUM CONNECTION      | Ø 80 Camlock  |
| TOTAL WEIGHT           | 590 kg/600 kg |
| LENGTH                 | 200 cm        |
| WIDTH                  | 69 cm         |
| HEIGHT                 | 110 cm        |
| TRANSPORT LENGTH       | 137 cm        |
| TRANSPORT WIDTH        | 69 cm         |
| TRANSPORT HEIGHT       | 110 cm        |
| ARTICLE NO.            | 680001/680000 |

### FEATURES:

- ✓ ENCLOSED DESIGN FOR MAXIMUM SERVICE LIFE
- ✓ PLANETARY GEARBOX, DIRECT DRIVE
- ✓ SPRAY SYSTEM, 25 L WATERTANK
- ✓ ADJUSTABLE AND ERGONOMICALLY HANDLE
- ✓ DUST-FREE OPERATION
- ✓ PRECISE SPEED CONTROL
- ✓ LED LIGHTING
- ✓ ERGONOMIC TRANSPORT WHEEL
- ✓ ADJUSTABLE ADDITIONAL WEIGHTS POSSIBLE
- ✓ DUST PROTECTION INCLUDED
- ✓ INTEGRATED BATTERY



ALL MACHINES ARE CE CONFORM AND FULLY COMPLIANT WITH EU REGULATIONS.

[WWW.HTGEUROPE.COM](http://WWW.HTGEUROPE.COM)

HTG EUROPE