

HTG

680 ULTRA

TECHNICAL SHEET:

FLOOR GRINDER



GRINDING WIDTH	680 mm
GRINDING DISC DIAMETER	230 mm
NUMBER OF GRINDING HEADS	3 or 4
OUTPUT POWER	11,0 kW
VOLTAGE	400 V
RATED CURRENT	20 A
FREQUENCY	50/60 Hz
TYPE	Walk-behind
DIRECTION OF ROTATION	Right/Left
GRINDING HEAD SPEED MIN (RPM)	300
GRINDING HEAD SPEED MAX (RPM)	900

MAX. GRINDING PRESSURE	325 kg/335 kg
ELECTRICAL CONNECTION	32 A - 400 V
VACUUM CONNECTION	Ø 80 Camlock
TOTAL WEIGHT	560 kg/570 kg
LENGTH	200 cm
WIDTH	69 cm
HEIGHT	110 cm
TRANSPORT LENGTH	137 cm
TRANSPORT WIDTH	69 cm
TRANSPORT HEIGHT	110 cm
ARTICLE NO.	680003/680002

FEATURES:

- ✓ ENCLOSED DESIGN FOR MAXIMUM SERVICE LIFE
- ✓ PLANETARY GEARBOX, DIRECT DRIVE
- ✓ SPRAY SYSTEM, 25 L WATERTANK
- ✓ ADJUSTABLE AND ERGONOMICALLY HANDLE
- ✓ DUST-FREE OPERATION
- ✓ PRECISE SPEED CONTROL
- ✓ LED LIGHTING
- ✓ ERGONOMIC TRANSPORT WHEEL
- ✓ ADJUSTABLE ADDITIONAL WEIGHTS POSSIBLE
- ✓ DUST PROTECTION INCLUDED

ALL MACHINES ARE CE CONFORM AND FULLY COMPLIANT WITH EU REGULATIONS.

WWW.HTGEUROPE.COM



HTG EUROPE

