TECHNICAL SHEET:

HTG

680 ULTRA

FLOOR GRINDER



GRINDING WIDTH	680 mm	MAX. GRINDING PRESSURE	325 kg/335 kg
GRINDING DISC DIAMETER	230 mm	ELECTRICAL CONNECTION	32 A - 400 V
NUMBER OF GRINDING HEADS	3 or 4	VACUUM CONNECTION	Ø 80 Camlock
OUTPUT POWER	11,0 kW	TOTAL WEIGHT	425 kg/445 kg
VOLTAGE	400 V	LENGTH	200 cm
RATED CURRENT	20 A	WIDTH	69 cm
FREQUENCY	50/60 Hz	HEIGHT	110 cm
TYPE	Walk-behind	TRANSPORT LENGTH	137 cm
DIRECTION OF ROTATION	Right/Left	TRANSPORT WIDTH	69 cm
GRINDING HEAD SPEED MIN (RPM)	300	TRANSPORT HEIGHT	110 cm
GRINDING HEAD SPEED MAX (RPM)	900	ARTICLE NO.	680003/680002

FEATURES:

- ✓ENCLOSED DESIGN FOR MAXIMUM SERVICE LIFE
- ✓PLANETARY GEARBOX, DIRECT DRIVE
- ✓SPRAY SYSTEM, 25 L WATERTANK
- ✓ADJUSTABLE AND ERGONOMICALLY HANDLE
- ✓DUST-FREE OPERATION
- ✓PRECISE SPEED CONTROL
- ✓LED LIGHTING
- ✓ERGONOMIC TRANSPORT WHEEL
- ✓ADJUSTABLE ADDITIONAL WEIGHTS POSSIBLE
- ✓DUST PROTECTION INCLUDED

ALL MACHINES ARE CE CONFORM AND FULLY COMPLIANT WITH EU REGULATIONS.

CE

WWW.HTGEUROPE.COM

HTG EUROPE